

A: Datasheet

Algorithm: qnap_000

Developer: Qnap Security

Submission Date: 2021_07_28

Template size: 2048 bytes

Template time (2.5 percentile): 455 msec

Template time (median): 457 msec

Template time (97.5 percentile): 464 msec

Investigation:

Frontal mugshot ranking 165 (out of 329) -- FNIR(1600000, 0, 1) = 0.0078 vs. lowest 0.0009 from sensetime_006

Mugshot webcam ranking 166 (out of 291) -- FNIR(1600000, 0, 1) = 0.0274 vs. lowest 0.0057 from sensetime_006

Mugshot profile ranking 97 (out of 260) -- FNIR(1600000, 0, 1) = 0.5217 vs. lowest 0.0550 from sensetime_006

Immigration visa-border ranking 125 (out of 218) -- FNIR(1600000, 0, 1) = 0.0132 vs. lowest 0.0009 from sensetime_006

Immigration visa-kiosk ranking 124 (out of 215) -- FNIR(1600000, 0, 1) = 0.1582 vs. lowest 0.0487 from cubox_000

Identification:

Frontal mugshot ranking 210 (out of 329) -- FNIR(1600000, T, L+1) = 0.1289, FPIR=0.001000 vs. lowest 0.0017 from nec_005


Mugshot webcam ranking 196 (out of 289) -- FNIR(1600000, T, L+1) = 0.2379, FPIR=0.001000 vs. lowest 0.0120 from nec_005

Mugshot profile ranking 248 (out of 259) -- FNIR(1600000, T, L+1) = 1.0000, FPIR=0.001000 vs. lowest 0.1331 from cloudwalk_hr_000


Immigration visa-border ranking 146 (out of 217) -- FNIR(1600000, T, L+1) = 0.1908, FPIR=0.001000 vs. lowest 0.0032 from paravision_009

Immigration visa-kiosk ranking 188 (out of 212) -- FNIR(1600000, T, L+1) = 0.9980, FPIR=0.001000 vs. lowest 0.0728 from paravision_009


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (nec_005)




C: Evolution of accuracy for QNAP algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_006)




L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.
The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T , $N = 1.6$ million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: qnap_000, Dataset: Border–Crossing Ageing
Threshold: 0.582016 set to achieve FPIR(30–45, Male) = 0.001

Color encodes log(FPIR)



(The age of the highest non-mates will usually be similar to that of the probe.)

(60:99] 0.0055 0.0018

(45:60] 0.0029 0.0009

(30:45] 0.0027 0.0010

(21:30] 0.0047 0.0014

(18:21] 0.0066 0.0021

(15:18] 0.0064 0.0024

(12:15] 0.0057 0.0026

Female

Male

Sex of person in non-mate probe
(The sex of the highest non-mates will usually be that of the probe.)

Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

